

The Commander 8.0 - 26BF8M-CS-AD

4K bullet with color search & active deterrence



Features

- 1/2.8" Progressive Scan CMOS
- NDAA Compliant
- 8MP Resolution
- 30FPS
- 2.8mm lens
- 107° Viewing Angle
- Ultra Low Light Capable
- 130 Ft. IR Night Vision
- 130FT White Light
- Built in Mic and Speaker
- Red and Blue Active Lights
- IP67 Weatherproof
- ONVIF Profile S/T/G/M
- 3 Year Warranty
- 5 Year Warranty Option

Specifications

| Camera and Image | |
|-------------------------|---------------------------------------------------------------------------------|
| Image Sensor | 1/2.8" Progressive scan CMOS |
| Max Resolution | 3840×2160 |
| Effective Pixels | 8,294,400 Pixels |
| Frame Rate | 8MP/4K (3840×2160): Max. 30 fps |
| Lens | 2.8mm @ F1.0, angle of view ~107° |
| IR Distance | 130ft IR / 130FT White Light |
| Minimum Illumination | 0.001 lux @F1.0, AGC ON |
| Audio | Built in Microphone, Built in Speaker |
| Wide Dynamic Range | True WDR @ 130dB |
| Analytics | AI enhanced (people / vehicle detection) & color search (shirt / vehicle color) |
| General | |
| Onboard Storage | MicroSD - Up to 512GB (Card not included) |
| Image Settings | Full picture customization via web browser |
| Communication Interface | 1 RJ45 10M/100M Ethernet Interface |
| Compliance | FCC / UL / CE / NDAA Compliant |
| Interoperability | ONVIF Conformant - Profiles S, T, G |
| Power and Dimensions | |
| Power Supply | DC 12V(±25%), PoE (802.3af) |
| Power Consumption | Max. 10W |
| Weather Protection | IP67 Compliant |
| Operating Temperature | (-22°F ~ 140 °F) Humidity ≤95% (non-condensing) |
| Mounting Box | EMB26BV |
| Dimensions | 10.6" × 3.8" × 3.2" |
| Weight | 2.14lb |



For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email hello@getscw.com

www.getscw.com