

Observer 5.0 Multi-Sensor - 26DV5-MS

5MP 4 sensor, 4x vari-focal camera



Features

- 4x 1/2.7" P-Scan CMOS
- NDAA Compliant
- 5MP@30FPS Resolution
- 2.7-13.5mm
- 110-31° Viewing Angle
- IK10 Impact Resistant
- AI Enhanced analytics
- **Single Ethernet Connection**
- PoE Injector Included
- 165 Ft. Night Vision
- IP67 Weatherproof
- IK10 Impact Resistant
- ONVIF Profile S/T/G/M
- 3 Year Warranty
- 5 Year Upgrade Avail



Camera and Image	
Image Sensor	4x 1/2.7" Progressive scan CMOS
Max Resolution	2880x1620
Frame Rate	30FPS Each Sensor
Lens	2.7 - 13.5 Vari-focal (110-31° FOV)
IR Distance	8+1 LEDs - Up to 165FT
Minimum Illumination	0.001 lux @F1.2
Electronic Shutter	Auto/Manual, 1 ~ 1/100,000s
Wide Dynamic Range	130dB True WDR
VCA	AI Enhanced (Person/Vehicle detection)
Communication	
Onboard Storage	MicroSD - Up to 512GB (Card not included)
Communication Interface	1 RJ45 10M/100M/1000M Ethernet Interface
Interoperability	ONVIF Conformant - Profiles S, G, T & M
Compliance	FCC / UL / CE / NDAA Compliant
Audio	2x Built in Mics - Audio on all 4 sensors
I/O	Audio and Alarm Input/Output Terminal
Power and Dimensions	
Power Supply	AC or DC 24V(±25%) 802.3bt PoE++ (Injector included)
Power Consumption	49W
Weather Protection	IP67 Compliant
Impact Resistance	IK10 Impact and Vandal Resistant
Operating Temperature	(-22°F ~ 140 °F) Humidity <95% (non-condensing)
Mounting Adapter Plate	26OAP
Dimensions	Φ 12.52" x 5.38"
Weight	10.5LB

For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email hello@getscw.com

www.getscw.com