

The Lookout 2.0 Mini - 26ZV-MINI-L

1080p 4x PTZ with active deterrence



Features

- 1/2.8" P-Scan CMOS
- 1080p@30FPS Resolution
- 4x Zoom
- 2.8-12mm Lens
- 95.7-32.5° Viewing Angle
- Built in Mic & Speaker
- Built in strobe light
- Audio warnings
- 165 Ft. Night Vision
- IP66 Weatherproof
- Mac Support
- ONVIF Profile S/G/T
- 3 Year Warranty



Camera and Image	
Image Sensor	1/2.8" Progressive scan CMOS
Max Resolution	1920 x 1080
Effective Pixels	2,073,600 Pixels
Frame Rate	30FPS at 1080p
Lens	2.8-12mm - Angle of View: 95.7-32.5°
PTZ Specs	345° Pan Range,
IR Distance	165FT
Minimum Illumination	0.001 lux (F1.6,AGC ON) 0 lux with IR
Electronic Shutter	1/30s ~ 1/100,000s
White Balance	Auto white balance
BLC	BLC with Zone Configurable Options
Wide Dynamic Range	True 120dB WDR
Noise Reduction	3DNR
Communication	
Audio	Built in Microphone and Speaker
Communication Interface	1 RJ45 10M/100M Ethernet Interface
Interoperability	ONVIF Conformant - Profiles S, G & T
Power and Dimensions	
Power Supply	DC 12V±25%, PoE (IEEE802.3 at)
Power Consumption	Max. 16W
Weather Protection	IP66 Compliant
Operating Temperature	(-4°F ~ 140 °F) Humidity <95% (non-condensing)
Dimensions	Φ5.2"x 9.8"
Mount	Arm mount built in
Weight	2.49 pounds

For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email hello@getscw.com

www.getscw.com