

The Watchkeeper 4.0 v2 - 26ZV4M

4MP 25x Long Range NDAA Compliant PTZ



Features

- 1/2.8" Progressive Scan CMOS
- NDAA Compliant M-Star CPU
- 4MP Resolution
- 30FPS
- 25x Zoom
- PoE+
- 4.8-120mm Motorized Lens
- 52-2.7° Angle of View
- 325Ft. IR Night Vision
- Audio and Alarm I/O
- IP67 Weatherproof
- IK10 Impact Resistant
- ONVIF Profile S/T/G
- 3 Year Warranty
- 5 Year Warranty Option



Camera and Image	
Image Sensor	1/2.8" Progressive scan CMOS
Max Resolution	2688x1520
Effective Pixels	4,085,760 Pixels
Frame Rate	30FPS @ 4MP
Lens	4.8-120mm, 52.20 - 2.74°
IR Distance	325FT
Minimum Illumination	0.003 Lux (F1.5, AGC ON)
Electronic Shutter	Auto/Manual 1 ~ 1/100000s
Wide Dynamic Range	True WDR @ 120dB
PTZ Specs	
Pan Range & Speed	360° (Endless) 0.1°/s ~ 200°/s
Tilt Range & Speed	-15° ~ 90° (auto reverse) 0.1°~ 120°/s
Preset Speed & Amount	240°S Pan - 200°/s Tilt & Up to 1024
Communication	
Onboard Storage	MicroSD up to 256GB (card not included)
Communication Interface	1 RJ45 10M/100M Ethernet Interface
Interoperability	ONVIF Conformant - Profiles S, T, G
Compliance	FCC / UL / CE / NDAA Compliant
Power and Dimensions	
Power Supply	DC12V(±25%) 3A - PoE+ (802.3at) injector not required or included. Ensure your PoE switch or NVR can provide adequate power.
Power Consumption	Max. 21W
Weather Protection	IP67 Compliant
Impact Protection	IK10 Impact Rated
Operating Temperature	(-40°F ~ 158 °F) Humidity <95% (non-condensing)
Dimensions	Ø6.5" x 11.6"
Weight	6.72lb

Updated 1/2025 - For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email hello@getscw.com

www.getscw.com