

# The Lookout 5.0 Mini - 26ZV5M-MINI

5mp 4x PTZ with active deterrence



## Features

- 1/2.7" P-Scan CMOS
- NDAA Compliant
- 5MP@30FPS Resolution
- 4x Zoom
- 2.8-12mm Lens
- 104-30.6° Viewing Angle
- Built in Mic & Speaker
- Built in strobe light
- Audio warnings
- 165 Ft. Night Vision
- 30 Ft. White Light
- IP66 Weatherproof
- ONVIF Conformant
- 3 Year Warranty



Camera and Image	
Image Sensor	1/2.7" Progressive scan CMOS
Max Resolution	2880x1620
Effective Pixels	4,665,600 Pixels
Frame Rate	30FPS at 5MP
Lens	2.8-12mm - Angle of View: 104.1-30.6°
PTZ Specs	345° Pan Range
IR Distance	165FT
Minimum Illumination	0.003 lux (F1.6,AGC ON) 0 lux with IR
Electronic Shutter	1 s ~ 1/100000 s
Wide Dynamic Range	True 120dB WDR
Analytics	AI Enhanced - People & Vehicle Detection
Communication / Alerts	
Audio	Built in Microphone and Speaker
Communication Interface	1 RJ45 10M/100M Ethernet Interface
Interoperability	ONVIF Profile S, T & G
Compliance	FCC / UL / CE / NDAA Compliant
Active Deterrence	Audio Warnings, Red/Blue light, White Light
Alerts set by	VCA Intrusion Detection / Cross Line
Power and Dimensions	
Power Supply	DC 12V±25%, PoE (IEEE802.3 at)
Power Consumption	Max. 18W
Weather Protection	IP66 Compliant
Operating Temperature	(-4°F ~ 140 °F) Humidity <95% (non-condensing)
Dimensions	Φ5.2"x 10.6"
Mount	Arm mount built in
Weight	2.49 pounds

Updated 1/2025 - For More Information Contact SCW

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email [hello@getscw.com](mailto:hello@getscw.com)

[www.getscw.com](http://www.getscw.com)