

The Spotter 3.0 - 44330

2.8-12mm Motorized, IntelliPro Bullet Cam



Features

- 1/2.8" P-Scan CMOS
- 3.0MP 30FPS
- 8mm-12mm Motorized Zoom
- 98° to 30.5° Viewing Angle
- 150 Ft. Night Vision
- IP67 Weatherproof
- On Board MicroSD Slot
- Mac Support
- ONVIF, PSIA, CGI Support
- 3 Year Warranty

Specifications

Camera and Image	
Image Sensor	1/2.8" Progressive scan CMOS
Max Resolution	2048 x 1536
Effective Pixels	3,145,728 Pixels
Frame Rate	30FPS at 3MP - 60FPS at 1080p
Lens	Motorized Zoom and Focus, 2.8-12mm
Camera Body Color	White
IR Distance	150FT
Minimum Illumination	0.001 Lux @ (F1.4, AGC ON), 0 Lux with IR
Electronic Shutter	1s ~ 1/100,000s
White Balance	ATW
BLC	BLC with Zone Configurable Options
Wide Dynamic Range	Digital WDR
Noise Reduction	3DNR
Communication	
Image Settings	Full picture customization via web browser
Communication Interface	1 RJ45 10M/100M Ethernet Interface
On-Board Storage	Micro-SD Up to 128GB - (Not Included)
Interoperability	ONVIF, PSIA, CGI
Power and Dimensions	
Power Supply	AC24V ± 10% , PoE (802.3at)
Power Consumption	Max. 18W
Weather Protection	IP 67 Compliant
Operating Temperature	-40F to 140°F at 90% Humidity or less (non-condensing)
Dimensions	3.93"x4.09"x12.28"
Weight	4.1 lbs



For More Information Contact Security Camera Warehouse

Toll Free: 1.866.414.2553 • Fax 1.866.337.9542 • Email sales@security-camera-warehouse.com

www.security-camera-warehouse.com