

The Logos - FDMD

Fever and Metal detector gate



Key Features

- High sensitivity metal detector
- Adjustable sensitivity levels
- Non contact measurement
- Real time temperature display
- Real time alarm
- $\leq +0.54^{\circ}\text{F}$ Accuracy
- 1-3cm measuring distance
- 7" Touchscreen & 5.7 inch LCD
- Modular Design
- 3 Year Warranty



Metal Detector Specs	
Detection zones	18 detection zones
Detection sensitivity	0-255 levels for each zone
Remote Control	Standard IR control for remote operations
Counting	Counts people & can alarm based on number
Thermometer Specs	
Measurement Area	Wrist
Measurement Distance	1-3cm
Precision	0.18°F
Measurement Deviation	$\pm 0.54^{\circ}\text{F}$
Measurement Range	86°F to 113°F
Display & Alarms	
Display	7" Touch Screen & 5.7 Inch LCD
Alarm Type	Local sound & Lights alarm
Physical Specs	
External Dimensions	87.40 x 32.87 x 22.75 inches
Internal Dimensions	78.3 x 27.55 x 22.75 inches
Power & Environment	
Power Supply	AC 100-240V
Operating Temperature	59°F to 86°F
Operating Humidity	<80%, non-condensing
Application	Indoor only - windless